



SYNCRO+

- 600VA/800VA standby UPS
- High frequency design
- Compact size with stand and mounting flexibility
- Suitable for active PFC equipped personal computers
- Auto restart while AC is recovering
- Simulated sine wave output
- Cold start function
- USB communication port
- NEXTVision shutdown software suite
- 3 years NEXT Onsite warranty



SYNCRO+ Off-Line UPS Selection Guide

MODEL	SYNCRO+ 600	SYNCRO+ 800
CAPACITY	600 VA / 360 W	800 VA / 480 W
INPUT		
Voltage	220/230/240 VAC	
Acceptable Voltage Range	180 - 270 VAC	
Frequency	50Hz or 60Hz (Auto sensing)	
OUTPUT		
Output Voltage	220/230/240 VAC	
Voltage Regulation (Batt. Mode)	± 10%	
Frequency Range (Batt. Mode)	50Hz / 60Hz ± 1 Hz	
Transfer Time (Typical)	2-6 ms	
Waveform (Batt. Mode)	Simulated Sinewave	
BATTERY		
Battery Type & Number	12 V / 7 Ah x 1	12 V / 9 Ah x 1
Typical Recharge Time	8 hours recover to 90% capacity	
INDICATORS		
AC Mode	Green lighting	
Battery Mode	Green flashing every 10 seconds	
Low Battery (Batt. Mode)	Green flashing every second and red lighting	
Fault	Red lighting	
ALARM		
Battery Mode	Sounding every 10 seconds	
Low Battery (Batt. Mode)	Sounding every second	
Fault	Continuously sounding	
PHYSICAL		
Dimension, D x W x H (mm)	228 x 82.5 x 207 (vertically stand)	
Net Weight (kgs)	2.7	3.1
ENVIRONMENT		
Humidity	0-90 %	
Operating Temperature	0- 40°C (non-condensing)	
MANAGEMENT		
USB Port	NEXTVision Supports Windows® 2000/2003/XP/Vista/2008, Windows® 7/8, Linux, Unix, and MAC	
NEXT PARTNUMBERS		
SYNCRO+ IEC	22311	22312
SYNCRO+ BE/FR	22314	22315
SYNCRO+ NL/LU	22317	22318
NEXT 5+ warranty extension	11002	11002

Product specifications are subject to change without further notice